

TECHNICAL SPECIFICATIONS

T24

PRODUCTION TOURING CARS

2.2 PRODUCTION (T24)

2.2.1 All cars must comply with the following specifications at the commencement of and during each event:

2.2.2 CARS

2.2.2.1 Cars shall have a maximum overall width of 83mm.

2.2.2.2 Cars shall have a maximum height of 40mm measured from the track surface.

2.2.2.3 No part of the car, except braids, tyres and skids, shall touch the track when stationary.

2.2.3 BODIES

2.2.3.1 Bodies shall be Commercially Available 1/24th closed road-going touring/saloon, sports or GT semi-scale bodies. (These are generally listed by manufacturers such as DTM bodies.)

2.2.3.2 **Bodies must be cut according to the specifications below:**

2.2.3.2.1 A minimum height of 21mm, measured from the track surface to where the bottom of the windscreen meets the hood/bonnet.

2.2.3.2.2 A maximum height of 40mm, measured from the track surface.

2.2.3.3 Bodies shall be painted or otherwise finished in a presentable manner, with transparent windscreen and windows where applicable.

2.2.3.4 Bodies shall have cut out or clear wheel arches which at least correspond in position and size with the wheels on the chassis. Not applicable if a wheel decal or painted wheel facsimile are used.

2.2.3.5 Front-wheel decals or a reasonable hand-drawn/painted facsimile ± 16 mm in diameter may be applied instead of chassis-mounted front wheels. These must correspond to the position of the front wheels as provided on the body shell.

2.2.3.6 Bodies shall have, in the appropriate position, a presentably painted 2 or 3-dimensional driver consisting of the head, shoulders, hands and the upper half of a steering wheel.

2.2.3.7 Bodies shall clearly display two racing numbers, with a minimum height of 6mm; numbers will be issued based on the results of the Open Class from the previous season. The organisers will allocate racing numbers to overseas entrants.

2.2.4 CHASSIS

2.2.4.1 Chassis must be a Commercially Available formed and stamped steel chassis and be homologated by SAMCA for competition.

- 2.2.4.2 Chassis currently homologated are from the following manufacturers:
JK Products and Mossetti Racing.
- 2.2.4.3 **No filing, cutting or structural alteration of the chassis is permitted other than those detailed below:**
 - 2.2.4.3.1 Pillow blocks may be braced.
 - 2.2.4.3.2 A gear guard may be added.
 - 2.2.4.3.3 A guide flag mount may be reinforced.
 - 2.2.4.3.4 A motor brace may be added.
 - 2.2.4.3.5 The holes to locate the motor may be filed to facilitate alignment.
- 2.2.4.4 Weight may be added to the top of the chassis, but magnetic traction aids are not permitted.
- 2.2.4.5 The original Bite Bar may be substituted with a Bite Bar of a different material, diameter and/or shape.
- 2.2.4.6 The motor may be soldered to the chassis.
- 2.2.4.7 Chassis shall not project from the body or be visible when viewed from above.
- 2.2.4.8 Rear axle ball bearings are permitted.
- 2.2.4.9 Skids may be added to the front of the chassis but must conform to the shape and size of the chassis.
- 2.2.4.10 Floating or fixed body pin tubing may be added.

2.2.5 GUIDE

- 2.2.5.1 The guide shall be made from a plastic, nylon or other non-metallic material.
- 2.2.5.2 The guide shall present a smooth surface to the slot and have no sharp edges, which could damage the track surface.
- 2.2.5.3 The guide pivot mounting shall be fixed and centred on the chassis when viewed from the front.
- 2.2.5.4 The guide shall have a maximum length of 28mm and may penetrate the slot by no more than 6.35mm.
- 2.2.5.5 The guide shall be fully enclosed by the body used.
- 2.2.5.6 Weighted guides are not permitted.

2.2.6 TYRES

- 2.2.6.1 Driving wheels shall be fitted with black tyres made from sponge rubber.
- 2.2.6.2 If non-driving wheels are fitted, the tyres shall be made from rubber or similar material and must be visible from the sides.

2.2.7 AIRDAMS & SPOILERS

- 2.2.7.1 No additional aerodynamic devices may be fitted.

2.2.8 MOTORS

- 2.2.8.1 All commercially available "D" Can motors and components are permitted.
- 2.2.8.2 Only manufacturer tagged "16D" or "S16D" armatures are permitted. Such armatures may be hand-wound and have drill blank shafts.
- 2.2.8.3 Brushes may be shunted.
- 2.2.8.4 Can and endbell ball bearings may be fitted.